

```

1  <!--
2  Chris Burbine question posted to Piazza
3  https://piazza.com/class/hi2cfz0f9096iw?cid=61
4  updated by JMH on November 3, 2013 at 12:25 PM to correct buçs
5  updated by JMH on October 28, 2015 at 10:55 PM to improve layout and add <label for> elements
6  -->
7  <!DOCTYPE html >
8  <html >
9  <head >
10 <title></title>
11 <meta http-equiv="Content-Type" content="text/html" charset=UTF-8">
12 <script src="//ajax.googleapis.com/ajax/libs/jquery/2.1.4/jquery.min.js"></script>
13 <!--
14 <script src="jquery-validation-1.11.1/dist/jquery.validate.min.js"
15     type="text/javascript"></script>
16 -->
17 <script src="/-heines/jQuery/plugins/jquery-validation-1.11.1/jquery.validate.min.js"
18     type="text/javascript"></script>
19 <script>
20 $(document).ready(function() {
21     $.validator.addMethod('lessThanEqual', function(value, element, param) {
22         // debugging code added by Jesse
23         console.log("value = " + value + " (" + typeof(value) + ")"); // value = 1 (string)
24         console.log("element = " + element + " (" + typeof(element) + ")"); // element = [object HTMLInputElement] (object)
25         console.log("$.element.val() = " + $.element.val()); // $.element.val() = 1
26         console.log("param = " + param + " (" + typeof(param) + ")"); // param = 10 (number)
27         console.log("this.optional(element) = " + this.optional(element)); // this.optional(element) = false
28
29         // Chris's original code
30         // return this.optional(element) || parseInt(value) <= parseInt($.param().val());
31
32         // Jesse's corrected code
33         return this.optional(element) || parseInt(value) <= param;
34     }, "The value must be less than {0}.");
35
36     $('#frm').validate({
37         rules: {
38             first: {
39                 number: true,
40                 lessThanEqual: 10 // corrected by Jesse, was true
41             },
42             second: {
43                 number: true
44             }
45         }
46     });
47 });
48 </script>
49
50 <style> /* format the error messages */
51 .error {
52     color: red;
53     font-style: italic;
54 }
55 </style>

```

```
56 </head>
57 <body>
58   <!--
59     Note the use of <label for></label > elements with class="error" to control
60     where error messages will be displayed.
61   -->
62   <form name="frm" id="frm" method="GET" action="">
63
64     <!-- first input field -->
65     <p>Please enter a number less than 10: <br>
66     <input type="text" name="first" id="first">&nbsp;
67     <label for="first" class="error"></label ></p>
68
69     <!-- second input field -->
70     <p>Enter any number you like: <br>
71     <input type="text" name="second" id="second">&nbsp;
72     <label for="second" class="error"></label ></p>
73
74     <!-- submit button -->
75     <input type="submit" value="Go!">
76
77   </form>
78 </body>
79 </html >
```