w3schools   Menu ▾   Log in

☰   🏠   HTML   CSS   ◑   🌐   🔍

CSS :visited Selector

[‹]   [Selectors]   [›]

Example

Select and style visited links:

```
a:visited {
    color: pink;
}
```

Try it Yourself »

More "Try it Yourself" examples below.

Definition and Usage

The `:visited` selector is used to select visited links.

Tip: Use the :link selector to style links to unvisited pages, the :hover selector to style links when you mouse over them, and the :active selector to style links when you click on them.

Browsers limits the styles that can be set for a:visited links, due to security issues.

Allowed styles are:

- color
- background-color
- border-color (and border-color for separate sides)
- outline color
- column-rule-color
- the color parts of fill and stroke

All other styles are inherited from a:link.

Version:	CSS1

Browser Support

The numbers in the table specifies the first browser version that fully supports the selector.

Selector	Chrome	Edge	Firefox	Safari	Opera
:visited	4.0	7.0	2.0	3.1	9.6

CSS Syntax

```
:visited {
  css declarations;
}
```

ADVERTISEMENT

More Examples

Example

Select and style unvisited, visited, hover, and active links:

```css
/* unvisited link */
a:link {
  color: green;
}

/* visited link */
a:visited {
  color: green;
}

/* mouse over link */
a:hover {
  color: red;
}

/* selected link */
a:active {
  color: yellow;
}
```

Try it Yourself »

Example

Style links with different styles:

```css
a.ex1:hover, a.ex1:active {
  color: red;
}

a.ex2:hover, a.ex2:active {
```

```
    font-size: 150%;
}
```

Try it Yourself »

Related Pages

CSS tutorial: CSS Links

CSS tutorial: CSS Pseudo classes

‹   Selectors   ›

ADVERTISEMENT