



<ins>	Defines inserted text cite, datetime
<keygen>	Defines a generated key in a form autofocus, challenge, disabled, form, keytype, name
<kbd>	Defines keyboard text
<label>	Defines an inline sub window for, form
<legend>	Defines a title in a fieldset
	Defines a list item value
<link>	Defines a resource reference href, hreflang, media, rel, sizes, type
<map>	Defines an image map name
<mark>	Defines marked text
<menu>	Defines a menu list label, type
<meta>	Defines meta information charset, content, http-equiv, name
<meter>	Defines measurement within a predefined range high, low, max, min, optimum, value
<nav>	Defines navigation links
<noframes>	Used to display text for browsers that do not handle frames
<noscript>	Defines a noscript section
<object>	Defines an embedded object data, form, height, name, type, usemap, width
	Defines an ordered list reversed, start
<optgroup>	Defines an option group label, disabled
<option>	Defines an option in a drop-down list disabled, label, selected, value
<output>	Defines some types of output for, form, name
<p>	Defines a paragraph
<param>	Defines a parameter for an object name, value
<pre>	Defines preformatted text
<progress>	Defines progress of a task of any kind max, value
<q>	Defines a short quotation cite
<rp>	Used in ruby annotations to define what to show browsers that do not support the ruby element
<rt>	Defines explanation to ruby annotations
<ruby>	Defines ruby annotations
<s>, <strike>	Used to define strikethrough text.
<samp>	Defines sample computer code
<script>	Defines a definition list async, type charset defer, src
<section>	Defines a section cite
<select>	Defines a selectable list autofocus, disabled, form, multiple, name, size
<small>	Defines small text
<source>	Defines media resources media, src, type
	Defines a section in a document
	Defines strong text
<style>	Defines a style definition type, media, scoped
<sub>, <sup>	Defines sub/super-scripted text
<table>	Defines a table summary
<tbody>	Defines a table body summary
<td>	Defines a table cell colspan, headers, rowspan
<textarea>	Defines a text area autofocus, cols, disabled, form, maxlength, name, placeholder, readonly, required, rows, wrap
<tfoot>, <thead>	Defines a table footer / head
<th>	Defines a table header colspan, headers, rowspan, scope
<time>	Defines a date/tim datetime
<title>	Defines the document title
<tr>	Defines a table row datetime
<tt>	Used to define teletype text
<u>	Used to define underlined text
	Defines an unordered list
<var>	Defines a variable
<video>	Defines a video autobuffer, autoplay, controls, height, loop, src, width

HTML5 TAG CHEAT SHEET

Created by WebsiteSetup.org